

619.00 EUR  
incl. 19% VAT, plus [shipping](#)



- Fanless Black Aluminum Enclosure
- Intel LGA1151 Socket 6th/7th Gen. Pentium, Core i3/i5/i7 35W Processors
- Supports DDR4-2133MHz SODIMM up to 32GB
- Supports up to 3 Independant Displays (HDMI \* 1 & DP \* 2)
- 1 \* 2.5" SATA3 6Gb/s Internal Drive Bay
- 1 \* Full-size mSATA/Mini PCIe Shared Slot
- Support TPM function (option)
- 4 \* USB 3.0 Ports, 2 \* USB 2.0 Ports
- 6\* Serial Ports (COM2 support RS232/422/485)
- Watchdog Timer, 19V/120W AC Adapter
- Includes Wall Mount bracket and DIN Rail Clips
- 264 (W) x 199.4 (D) x 58 (H) mm

|             |                                                                                                                                                            |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model    | JNF697-Q170 / MINI-ITX                                                                                                                                     |
| Part No     | <ul style="list-style-type: none"> <li>• HBJC501F697-Q170-B (non-WIFI)</li> <li>• HBJC501F697W-Q170-B (WIFI)</li> </ul>                                    |
| BIOS        | • AMI 16MB SMT Flash ROM                                                                                                                                   |
| CPU/Chipset | <ul style="list-style-type: none"> <li>• INTEL® LGA 1151 Socket 6th/7th Gen. Core i7 / i5 / i3 / Pentium 35W CPU</li> <li>• INTEL® Q170 chipset</li> </ul> |
| Memory      | • 2 * Dual channel DDR4-2133MHz SO-DIMM up to 32GB                                                                                                         |
| Storage     | <ul style="list-style-type: none"> <li>• 1 * 2.5" SATA3 6Gb/s internal drive bay</li> <li>• 1 * Full-size mSATA/mini-PCI Express shared slot</li> </ul>    |
| Network     | • 2 * Intel GbE (i219LM,i211AT)                                                                                                                            |

|                 |                                                                                                                                                                                                                                                                 |
|-----------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Rear Panel I/O  | <ul style="list-style-type: none"> <li>• 4 * USB 3.0 ports</li> <li>• 1 * HDMI , 2 * DP</li> <li>• 2 * RJ45</li> <li>• Line-in, Line-out, Mic</li> <li>• 6 * COM (COM2 support RS232/422/485)</li> <li>• 2 * Antenna holes</li> <li>• 1 * DC-in jack</li> </ul> |
| Front Panel I/O | <ul style="list-style-type: none"> <li>• 1 * Power button</li> <li>• 1 * HDD LED</li> <li>• 2 * USB 2.0 ports</li> </ul>                                                                                                                                        |
| Power Source    | • 19V 6.3A 120W AC to DC Adapter                                                                                                                                                                                                                                |
| Compliance      | • CE, FCC, RoHS, ErP Ready                                                                                                                                                                                                                                      |
| Temperature     | <ul style="list-style-type: none"> <li>• Operating Temperature: 0 ~ 40 ° C</li> <li>• Storage Temperature: -10 ~ 75 ° C</li> </ul>                                                                                                                              |
| Dimensions      | • 260 (W) x 208 (D) x 58.5 (H) mm                                                                                                                                                                                                                               |
| Packing         | <ul style="list-style-type: none"> <li>• Net Weight: 4.2KG</li> <li>• Gross Weight: 5KG</li> <li>• Color Box dimension: 406 (W) * 148 (D) * 380 (H) mm</li> </ul>                                                                                               |
| OS Support      | • Windows 7, Windows 8.1, Windows 10, Linux                                                                                                                                                                                                                     |
| Accessories     | • Wall mount bracket & DIN Rail Clip                                                                                                                                                                                                                            |