999.00 EUR
incl. 19% VAT, plus shipping

- Fanless Black Aluminum Enclosure
- Support Intel LGA1151 Socket 6th & 7th generation Pentinum, Core i3, i5, i7 Processors, Up to 35W
- Support DDR4-2133 SODIMM up to 32GB
- Support 3 * HDMI
- Support 2 * 2.5” SATA HDD
- Support Onboard TPM IC
- Watchdog Timer, 120W 19V AC Adapter

MB Model	– JNF793-Q170 Series/ MINI-ITX
Part No	– HBFFF793-Q170-B (non-WIFI) / HBFFF793W-Q170-B (WIFI) – HBFFF793-Q170-T1 (TPM1.2, non-WIFI) / HBFFF793W-Q170-T1 (TPM1.2, WIFI) – HBFFF793-Q170-T2 (TPM2.0, non-WIFI) / HBFFF793W-Q170-T2 (TPM2.0, WIFI)
BIOS	– AMI 16MB SMT Flash ROM
CPU/Chipset	– Intel® LGA 1151 Socket 6th & 7th generation Core i7 / i5 / i3 /Pentinum CPU (35W) – Intel® Q170 chipset Notes : When the system runs, CPU will automatically adjust its working clock frequency according to changing workload.
Memory	– 2 * SO-DIMM slots / dual channel DDR4-2133 up to 32GB total
Storage	– 2 * 2.5” SATA3 6Gb/s internal drive bay – 1 * Full-size mSATA slot
Network	– 2 * Intel Gigabit LAN (i219LM,i211AT)
Expansion	– 1 * Half-size Mini-PCI Express shared slot (for WIFI module)
Rear Panel I/O	– 4 * USB 3.0 ports – 3 * HDMI – 2 * RJ45 – Line-in, Line-out, MIC – 2 * COM (RS232/422/485), 4 * COM (RS232/optional) – 1 * DC-In jack
Front Panel I/O	– 1 * Power button, 1 * HDD LED – 2 * USB 2.0 ports – 2 * 2.5” HDD Tray (Easy to replace the hard disk, does not support hot swap)

Power Source	– FSP AC to DC Adapter 19VDC-6.3A 120W
Compliance	– CE, FCC,LVDS, RoHS, ErP Ready
Temperature	– Operating Temperature: 0 ~ 40° C – Storage Temperature: -20 ~ 75° C
Dimensions	– 290 (W) x 207 (D) x 65 (H) mm
Packing	– Net Weight: 3.8KG – Gross Weight: 4.8KG
OS Support	– Windows 7, Windows 8.1, Windows 10, Linux
Warranty	– 2 Year limited warranty