



339.00 EUR  
incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.5Ghz
- FANLESS carpc system
- 12VDC based !
- Closed front !

CARTFT.COM



Support: [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.  
Celeron-M 1.7Ghz is recommended for fanless operation.

| CALU specifications   |  |
|-----------------------|--|
| Processor (supported) | Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher     |
| Memory                | Supports DDR 333/266 DIMM RAM<br>0.8" low profile<br>2x memory slots !<br>Maximum : 2 GB |
| Video                 | Intel Extreme Graphics 2<br>Supports up to 64MB DVMT video memory                        |
| Audio                 | Software AC '97 Audio CODEC  |

|                              |  |
|------------------------------|--|
| <b>Peripheral Connection</b> | Front :<br>1 x IEEE 1394 Firewire port<br>1 x USB 2.0 / 1.1 Port<br>1 x MIC Port<br>1 x Ear Phone output Jack<br>Power-on button<br>Reset button<br>Power-on and HDD LED<br><br>Rear :<br>1 x RS232 COM port<br>1 x parallel printer port<br>1 x RJ45 10/100Mb Fast Ethernet<br>1 x Line-Out output Jack<br>2 x USB 2.0 / 1.1 Ports<br>1 x 15 pin VGA<br>1 x 12v DC Power Jack input |
| <b>Storage</b>               | One 2.5 inch Hard Disk and 9.5mm high.<br>(Support Ultra DMA 33/66/100).   |
| <b>Weight &amp; Size</b>     | System approximately 3kg (fully equipped).<br>System Dimension: 155 x 255 x 55 mm  |
| <b>Power req.</b>            | 12V, 5A  |
| <b>Accessory</b>             |  |
| <b>Storage</b>               | Supports all 2.5" standard IDE hard drive, ATA-100/66/33.  |
| <b>Scope of supply</b>       | 110V/230V EU power supply<br>Barebone<br>CPU Kühlkörper  |

Graphics driver for 800x480 resolution : [Here](#)