



398.00 EUR

incl. 19% VAT, plus [shipping](#)

- For Celeron M 1.6Ghz
- FANLESS carpc system
- 12VDC based !
- 4x LAN ports

CARTFT.COM



**Support:** [Assembling Tutorial \[DE\]](#) | [Assembling Tutorial \[EN\]](#)

Fanless CarPC-barebone for use with Intel P4/Celeron M CPU.

Celeron-M 1.7Ghz is recommended for fanless operation.

CALU specifications	
<b>Processor (supported)</b>	Intel Pentium M processor or Celeron M processor (Dothan or Banias) 1.3GHz or higher
<b>Memory</b>	Supports DDR 400/333/266 DIMM RAM 0.8" low profile 2x memory slots ! Maximum : 2 GB
<b>Video</b>	Intel Extreme Graphics 2 Supports up to 64MB DVMT video memory
<b>Audio</b>	Software AC '97 Audio CODEC

<b>Peripheral Connection</b>	Front :  3 x RJ45 10/100Mb Fast Ethernet  1 x IEEE 1394 Firewire port  1 x USB 2.0 / 1.1 Port  1 x MIC Port  1 x Ear Phone output Jack  Power-on button  Reset button  Power-on and HDD LED   Rear :  1 x RS232 COM port  1 x parallel printer port  1 x RJ45 10/100Mb Fast Ethernet  1 x Line-Out output Jack  2 x USB 2.0 / 1.1 Ports  1 x 15 pin VGA  1 x 12v DC Power Jack input
<b>Storage</b>	One 2.5 inch Hard Disk and 9.5mm high.  (Support Ultra DMA 33/66/100).
<b>Weight &amp; Size</b>	System approximately 3kg (fully equipped).  System Dimension: 155 x 255 x 55 mm
<b>Power req.</b>	12V, 5A

**Accessory**

<b>Storage</b>	Supports all Standard Slim CD-ROM/DVD-ROM, CD-RW, DVD-RW Combo  Supports all 2.5" standard IDE hard drive, ATA-100/66/33.
<b>Scope of supply</b>	110V/230V EU power supply  Barebone  CPU Kühlkörper

Graphics driver for 800x480 resolution : [Here](#)